




HALOS B

107120.02



Features

Usage: Indoor
Installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: OPALE
Color: BLACK
Dimming: WITH ACCESSORY
Emergency: NO
L: Ø962mm
W: 40mm
H: 50mm
Made in: ITALY
Warranty: 5 years
Weight: 6.9kg

Tech Data

Appliance luminous flux: 10614lm
Direct luminous flux: 4130lm
Indirect luminous flux: 6484lm
IP: 40
Insulation class: III
Power supply voltage: MAX 1.8A
IK: 3
SELV: Si

Source

LED source: LED
LED power: 124W
Nominal luminous flux: 17796lm
Color temperature: 3000K
CRI: >90
Color tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 11th Oct 2017.

[View more product info](#)

HALOS B

107120.02

MOUNTING ACCESSORIES



HALOS: ROSONE ALIM. REMOTA BIA

105157.01



HALOS: ROSONE ALIM. REMOTA NERO

105157.02

ELECTRICAL ACCESSORIES




HALOS: ROSONE DOPPIA ALIM. REMOTA BIA

105158.01




HALOS: ROSONE DOPPIA ALIM. REMOTA NERO

105158.02



HALOS-B: COPPIA ALIM. ON/OFF REM.

107125.99



HALOS-B: COPPIA ALIM. DALI/PUSH REM.

107126.99

HALOS B

107120.02



HALOS-B: ROSONE ALIM. ON/OFF BI

107127.01



HALOS-B: ROSONE ALIM. ON/OFF NE

107127.02



HALOS-B: ROSONE-N ALIM. ON/OFF BIA

107129.01



HALOS-B: ROSONE-N ALIM. ON/OFF NERO

107129.02

DIMMABLE ACCESSORIES



HALOS-B: ROSONE ALIM. DALI/PUSH BI

107128.01



HALOS-B: ROSONE ALIM. DALI/PUSH NE

107128.02



HALOS-B: ROSONE-N ALIM. D/PUSH BI

107130.01

HALOS B

107120.02



HALOS-B: ROSONE-N ALIM. D/PUSH NE

107130.02



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · P.IVA 00536541204 · novalux.it
Company activities managed and coordinated by SLV GmbH

The present data sheet is property of Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to modify the document contents at any time, without advanced notice.