KEYLIGHT								
PRODUCT MATERIAL LIGHT SOURCE MODULE LIFETIME DRIVER COLORS (Δ)	Die-cast aluminium Bridgelux V8 Array Approx. 50.000 hours Including phase cut dimmable driver 5 = RAL 9005 black (a) 35 = RAL 9003 white + 9005 black							
BEAM ANGLE ADJUSTABLE SIZE	350° rotational 90° rotational spot head Ø100 X 103mm							
OPTIONS								



OPTIONS

DRIVER OPTIONS

500mA 7-10W Art. no.: 0110.500.40.2 DALI


500mA 7-10W Art. no.: 0110.500.30.2

INFORMATION



Full warranty only applies when fixture is purchased in combination with recommended driver.

1/10V



	ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
	Δ See colors									
	6022.027.30. Δ	V8 Array	Bridgelux	845lm	9,3W	9,2lm/W	2700K	>90	35.000 Hrs	500mA

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.

LOOK

